



Figure similar

MLFB-Ordering data

6SL3210-1NE23-2AG1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.90
Number of phases	3 AC	Offset factor $\cos \varphi$	0.95
Line voltage	380 ... 480 V ± 10 %	Efficiency η	0.97
Line frequency	47 ... 63 Hz	Sound pressure level (1m)	65 dB
Rated current (LO)	33.10 A	Power loss	0.35 kW
Rated current (HO)	27.00 A	Ambient conditions	
Output		Cooling	Internal air cooling
Number of phases	3 AC	Cooling air requirement	0.019 m ³ /s (0.671 ft ³ /s)
Rated voltage	400 V	Installation altitude	1000 m (3280.84 ft)
Rated current (LO)	32.00 A	Ambient temperature	
Rated current (HO)	26.00 A	Operation LO	-10 ... 40 °C (14 ... 104 °F)
Max. output current	52.00 A	Operation HO	-10 ... 50 °C (14 ... 122 °F)
Rated power IEC 400V (LO)	15.00 kW	Transport	-40 ... 70 °C (-40 ... 158 °F)
Rated power NEC 480V (LO)	20.00 hp	Storage	-40 ... 70 °C (-40 ... 158 °F)
Rated power IEC 400V (HO)	11.00 kW	Relative humidity	
Rated power NEC 480V (HO)	15.00 hp	Max. operation	95 % RH, condensation not permitted
Pulse frequency	4 kHz		
Output frequency for vector control	0 ... 200 Hz		
Output frequency for V/f control	0 ... 550 Hz		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM230

MLFB-Ordering data

6SL3210-1NE23-2AG1




Figure similar

Mechanical data		Connections	
Degree of protection		Line side	
IP20 / UL open type			
Size		Version	
FSC		Plug-in screw terminals	
Net weight		Conductor cross-section	
5.10 kg (11.24 lb)		6.00 ... 16.00 mm² (AWG 10 ... AWG 6)	
Width		Motor end	
140 mm (5.51 in)			
Height		Version	
355 mm (13.98 in)		Plug-in screw terminals	
Depth		Conductor cross-section	
165 mm (6.50 in)		6.00 ... 16.00 mm² (AWG 10 ... AWG 6)	

Converter losses to EN 50598-2*

Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	-68.73 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values

Max. motor cable length	
Shielded	25 m (82.02 ft)
Unshielded	100 m (328.08 ft)

Standards

Compliance with standards	UL, CE, C-Tick (RCM), KCC
CE marking	Low-voltage directive 2006/95/EC